



SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCES AND OF THE COMPANY

PRODUCT NAME	WiserShield™ Air Barrier 1130		
PRODUCT USE	Air and Vapor Barrier Commercial Coating		
MANUFACTURER'S NAME	CRC COATING TECHNOLOGIES INC.™		
	6254 Skyway Rd., PO Box 915 Smithville, ON L0R 2A0 info@crccoatings.com	TEL 289-448-0157 888-292-5565 FAX 905-527-0606	3909 Witmer Rd Ste 1014 Niagara Falls, NY 14305 crccoatings.com

2. HAZARDS IDENTIFICATION

 	GHS CLASSIFICATION: Flammability 5, Reactivity 5, Health 3
ROUTE OF ENTRY	Skin, eyes, inhalation.
CARCINOGENIC STATUS	Possible carcinogen in humans
TARGET ORGANS	Skin, eyes, lungs
HEALTH EFFECTS - EYE	Mists, vapors, or fumes from this material can cause eye irritation with tearing, redness, or a stinging or burning feeling
HEALTH EFFECTS - SKIN	May be harmful if absorbed through skin. May cause skin irritation with redness, itching, or burning feeling, as well as swelling of the skin
HEALTH EFFECTS - INGESTION	May be harmful if swallowed. If swallowed in large quantities, asphalt can obstruct the intestine.
HEALTH EFFECTS - INHALATION	May be harmful if inhaled. Asphalt fumes have been associated with irritation of eyes, nose, and throat. Also, respiratory effects have been reported. Hydrogen sulfide (H ₂ S) can evolve when this product is stored or handled at elevated temperatures above 750°F (400°C). H ₂ S can cause respiratory irritation and hypoxia. At low concentrations, H ₂ S has an odor of rotten eggs. At higher concentrations, H ₂ S odor is not apparent. DO NOT USE ODOR AS AN INDICATOR OF EXPOSURE TO H₂S.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients are Proprietary

4. FIRST AID MEASURES

FIRST AID - INHALATION	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Seek medical attention immediately.
FIRST AID - SKIN	Remove all contaminated clothing immediately. Wash off with soap and water but do not attempt to remove asphalt that adheres to skin before obtaining medical assistance. Wash contaminated clothing before re-use. If symptoms persist, seek medical attention immediately.
FIRST AID - EYE	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
FIRST AID - INGESTION	DO NOT induce vomiting. Seek medical attention immediately. Clean mouth with water and drink plenty of water afterwards. If a person vomits when lying on his back, place him in the recovery position.

INFORMATION FOR DOCTOR

Most important symptoms and effects, both acute and delayed.
 May cause skin irritation.
 May cause eye irritation.
 Indications of any immediate medical attention and special treatment needed. Treat symptomatically.

WISERSHIELD™ AIR BARRIER 1130

5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY	Not flammable or combustible in delivery form. Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.
EXTINGUISHING MEDIA	Do not use a solid water stream as it may spread and scatter materials in combination.
SPECIAL HAZARDS OF PRODUCT	Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors, and fumes.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	Keep unnecessary people away, isolate hazard area and deny entry. Fight fire for other material that is burning. Avoid contact with this material during firefighting operations. Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.
EXPLOSION DATA - SENSITIVITY TO IMPACT	May form explosive mixture with air when heated above flashpoint.
EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE	Slight chance of static initiated explosion; especially when heated above flashpoint.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Do not let product enter drains or other waterways.
PERSONAL PRECAUTIONS	Isolate area. Avoid breathing vapors or mists. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard on some surfaces. Use appropriate safety equipment. Ensure adequate ventilation. Carefully contain and stop the source of the spill if safe to do so. Protect bodies of water by diking, absorbents, or absorbent boom if possible. Authorities should be notified if reportable quantity release occurs.
ENVIRONMENTAL PRECAUTIONS	Deluge spills with a 10% salt or brine solution to solidify solids. Soak up exuded liquids with inert absorbent material and collect in ventilated waste container for disposal.

REFERENCES TO OTHER SECTIONS

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment

See Section 13 for disposal information

7. HANDLING AND STORAGE

HANDLING	Use only in well-ventilated areas. Avoid contact with skin and eyes. Avoid formation of dusts and aerosols. Do not smoke near areas where material is handled or stored. The product should only be used in areas where electrical classification meets the product rating for this product, i.e., intrinsically safe. Avoid contact with eyes, skin, and clothing. Do not swallow. Protect exposed skin with a barrier cream or light mineral oil USP. Wash thoroughly after handling. See Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION.
STORAGE	Store in a dry place. Keep container tightly closed. Keep separate from incompatible substances (see below or Section 10 of the Safety Data Sheet).

INFORMATION ABOUT PROTECTION AGAINST EXPLOSION AND FIRE

Keep ignition sources away – Do not

Smoke Protect against electrostatic charges

SPECIFIC END USE(S)

No further relevant information available

WISERSHIELD™ AIR BARRIER 1130

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	Where available, emergency eye wash stations and safety showers are recommended in the immediate vicinity of use or handling. Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.
RESPIRATORY PROTECTION	Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or were indicated by your risk assessment process. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.
HAND PROTECTION	Use gloves constructed of chemical resistant materials, such as nitrile rubber if frequent or prolonged contact is expected. Protect exposed skin with a barrier cream or light mineral oil USP. Wash and dry hands after use.
EYE PROTECTION	Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Where available, an eye wash station is recommended immediately available to the work area.
BODY PROTECTION	Protect exposed skin with a barrier cream or light mineral oil USP. Where available, wear protective clothing such as disposable coveralls.
PROTECTION DURING APPLICATION	Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. DO NOT use gasoline, kerosene, solvents, or harsh abrasive skin cleaners to clean skin

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
ODOR & APPEARANCE	Slight Aromatic, Dark Brown to Black Liquid
ODOR THRESHOLD (ppm)	N/D
SPECIFIC GRAVITY	1.03
VAPOR DENSITY (AIR = 1)	N/D
VAPOR PRESSURE 20°C	Negligible at ambient temperature
EVAPORATION RATE	N/D
BOILING POINT (°C)	>100°C (212°F)
AUTOIGNITION TEMP (°C)	N/A
FREEZING POINT	<0°C (32°F)
pH	10.0 - 12.0
COEFFICIENT OF WATER/OIL DISTRIBUTION	N/D
SOLUBILITY IN WATER	Miscible
VOC (g/L)	0
FLASH POINT (PMCC) (°C/°F)	Not Applicable
UPPER FLAMMABLE LIMIT %VOL	Not Applicable
LOWER FLAMMABLE LIMIT %VOL	Non-flammable

10. STABILITY AND REACTIVITY

STABILITY	Stable at normal temperatures and pressures. Not normally reactive under recommended practices.
CONDITIONS TO AVOID	Strong oxidizing agents.
MATERIALS TO AVOID	Stable under normal conditions of use; however, incompatible with strong acids and strong oxidizers. Keep away from oxidizing agents and acidic products.
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	In case of fire hazardous decomposition products may be produced such as: Carbon oxides, hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures above 400°C (752°F). No decomposition products in case of appropriate storage / handling / transport.

11. TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE	No data available.
EFFECTS OF CHRONIC EXPOSURE	Possible carcinogen
EXPOSURE LIMITS	0.5 mg (m ³ asphalt)
IRRITANCY	May cause irritation
SENSITIZATION	May cause sensitization
CARCINOGENICITY	Possible carcinogen
REPRODUCTIVE TOXICITY	No information
TERATOGENICITY	No information
MUTAGENICITY	May be mutagenic (fumes)

WISERSHIELD™ AIR BARRIER 1130

12. ECOLOGICAL INFORMATION

MOBILITY	No data available.
PERSISTENCE / DEGRADABILITY	This product is estimated to have a slow rate of biodegradation.
BIO-ACCUMULATION	This product is not expected to bio accumulate through food chains in the environment.
ECOTOXICITY	Spills into water ways may be harmful to organisms and bottom feeders.

13. DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL	Recover as much product as possible for reuse. Dispose within RCRA regulations C40CFR 260 to CFR271
CONTAINER DISPOSAL	Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container reinstatement must be disposed of in compliance with applicable regulations.
UNCLEANED PACKAGING	Recommendation: Disposal must be made according to official regulations

14. TRANSPORTATION INFORMATION

HAZARD LABEL	
EXPORT	
DOT CFR 172 101 DATA	
UN PROPER SHIPPING NAME	Not Regulated
UN CLASS	
UN NUMBER	Not Regulated
UN PACKAGING GROUP	Not Regulated
FLASH POINT	Not Applicable
HAZARDOUS MATERIAL	Not Regulated
MARINE POLLUTANT	No
SPECIFIC PRECAUTIONS FOR USER	Appropriate advice on safety should accompany the package.

15. REGULATORY INFORMATION

WHMIS SYMBOL		
WHMIS CLASSIFICATION:	Not regulated	
CEPA STATUS (DSL):	No information available	

This product has been classified in accordance with the hazard criteria of Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.

Canada:	All components are in compliance with the Canadian Environmental Protection Act and are present on the domestic substances list. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.	
USA:	TSCA:	All components of this material are on the US TSCA inventory or are exempt.
	OSHA:	This material does not contain any hazardous components under OSHA regulation (29CFR 1910.1200).
	CERCLA:	This material does not contain any components with a section 304 EHS RQ.
	SARA TITLE 111: Section 302	No chemicals in this material are subject to the reporting requirements of the Section
	SARA TITLE 111: Section 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established per the Section
CA Prop 65:	WARNING! This product contains a chemical known to the State of California to cause cancer. Asphalt (CAS-No.8052-42-4)	

WISERSHIELD™ AIR BARRIER 1130

16. OTHER INFORMATION

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="background-color: #0000FF; color: white; padding: 2px;">HEALTH</td><td style="text-align: right; padding: 2px;">2</td></tr> <tr><td style="background-color: #FF0000; color: white; padding: 2px;">FLAMMABILITY</td><td style="text-align: right; padding: 2px;">0</td></tr> <tr><td style="background-color: #FFFF00; padding: 2px;">REACTIVITY</td><td style="text-align: right; padding: 2px;">0</td></tr> <tr><td style="padding: 2px;">PERSONAL PROTECTION</td><td style="text-align: right; padding: 2px;"><input type="checkbox"/></td></tr> </table>	HEALTH	2	FLAMMABILITY	0	REACTIVITY	0	PERSONAL PROTECTION	<input type="checkbox"/>	HMIS Hazard ID: 0-MINIMAL 1-SLIGHT 2-MODERATE 3-SERIOUS 4-SEVERE		NFPA Hazard ID: 0-MINIMAL 1-SLIGHT 2-MODERATE 3-SERIOUS 4-SEVERE
HEALTH	2										
FLAMMABILITY	0										
REACTIVITY	0										
PERSONAL PROTECTION	<input type="checkbox"/>										

Key	NA:	No applicable information found or available
	CAS#:	Chemical Abstracts Service Number
	ACGIH:	American Conference of Governmental Industrial Hygienists
	OSHA	Occupational Safety and Health Administration:
	PEL	Permissible Exposure Limit
	TLV	Threshold Limit Value
	STEL	Short Term Exposure Limit
	NTP	National Toxicology Program
	IARC	International Agency for Research on Cancer
	R	Risk
	S	Safety
	USP	US Pharmacopeia
LD50	Lethal Dose 50%	
PREPARED BY	CRC COATING TECHNOLOGIES INC.™	
SDS REVISION DATE	January 13, 2021	

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.