



PRODUCT DATA SHEET

ECOLOC 168

Dust Control & Liquid Tarp™

DESCRIPTION

ECOLOC 168 is a water-based emulsion. This emulsion is very stable, and will blend well with many fillers, fibers, and other anionic or nonionic dispersions. ECOLOC 168 is nonflammable and contains no toxic solvents.

BASIC USES

ECOLOC 168 is formulated to offer high performance dust management to loose aggregate and particulate related projects.

This professional product is designed for ease of application by trained crews and is provided as a concentrate that may be diluted with water depending on the application.

Used where a general emulsion is required in formulations for coating, sealants, and adhesives.

- Granular Roadbeds and Shoulders
- Granular Parking Lots
- Granular Mining and Forestry Roads
- Staging Areas
- Stockpiles and Tailings
- Dust Control

MAJOR ADVANTAGES

ECOLOC 168 is a safe alternative to hot-applied bitumen or solvent-based products

- Non-Water Soluble
- Excellent Dust Reduction
- Non-Leaching
- Ease of Application
- Non-Skid Surface
- Freeze/Thaw Resistant
- Environmentally Benign
- Salt Resistant
- VOC Free

TECHNICAL AND PRODUCT DATA

Percent Non-Volatile	52.2
pH	5-8
Specific Gravity	1.02
Odour	Sweetish
Viscosity	15 – 18sec Zahn #2
Volatile Organic Compounds	0 g/L
Colour	Dark Tan

PRECAUTIONS

This is an Industrial Product. Not for use by untrained personnel.

APPLICATION INSTRUCTIONS

This product is mildly alkaline. Before applying, read associated Safety Data Sheet and follow guidance on proper personal protective equipment and material handling

Do not store or use this material below 5°C

Do not store where exposed to direct sunlight

Refer to Application Data Sheet for Additional Precautions and Safe Handling Procedures

LIMITATIONS

Subject to damage if frozen. Information provided in this bulletin is intended as a guide only; potential users must base judgements on the suitability of this product on their own laboratory and field evaluations.

SHELF LIFE

Store up to 6 months in sealed containers. Keep containers tightly closed when not in use. KEEP FROM FREEZING.

CLEAN UP

Use water when wet or any suitable safety solvent when dry.

SPECIFICATIONS

OPSS 2510 – Ontario Provincial Standard Material Specification for Tall Oil Pitch Emulsion

SAFETY

FOR INDUSTRIAL USE ONLY. Keep out of reach of children. Refer to SDS for further information.

THIS PRODUCT IS NOT SUBJECT TO THE CONTROLLED PRODUCTS REGULATION

Effective: 14-Jul -2022

Replaces: 18-Jul-2013

WARRANTY DISCLAIMER

The information contained herein is based on available data and is provided for information only. CRC™ makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use therein. CRC™ will not be liable for any damages arising from the use of the information product described on this data sheet. Product data subject to change without notice. Unless otherwise stated, CRC™ sole warrantee shall be the replacement or refund of purchase price for any product found not to meet the above specifications.