



PRODUCT NAME: Ecoloc 168 Dust Control & Liquid Tarp™

DESCRIPTION

Ecoloc 168 Dust Control & Liquid Tarp™ is a water-borne emulsion coating formulated to offer high performance dust management to loose aggregate and particulate related projects. This professional product is designed for ease of application by trained crews and is provided as a concentrate that may be diluted with pH 7 potable water depending on the application.

For further information or to be provided a specification, please contact **CRC™ Coating Technologies**.

BASIC USES

- Granular Roadbeds and Shoulders
- Granular Parking Lots
- Granular Mining and Forestry Roads
- Staging Areas
- Stockpiles and Tailings
- Dust Control

MAJOR ADVANTAGES OF CRC™ Ecoloc 168 Dust Control & Liquid Tarp™

- Safe alternative to hot-applied bitumen or solvent-based products
- Non-water soluble
- Excellent dust reduction
- Non-leaching
- Ease of application
- Non-skid surface
- Freeze/Thaw Resistant
- Environmentally Benign
- Salt resistant
- VOC free

TECHNICAL AND PRODUCT DATA

Percent Non-Volatile 52.2
 pH 6-9
 Specific Gravity 1.02
 Odor Slight Sweet
 Viscosity..... 15 – 18sec Zahn #2
 Volatile Organic Compounds 0 g/L
 Color Dark Tan

SPECIFICATIONS

OPSS 2510 – Ontario Provincial Standard Material Specification for Tall Oil Pitch Emulsion.

PRECAUTIONS

This is an Industrial Product. Not for use by Untrained Personnel

APPLICATION INSTRUCTIONS

- This product is mildly alkaline. Before applying, read associated Safety Data Sheet and follow guidance on proper personal protective equipment and material handling
- Do not store or use this material below 41°F (5°C)
- Do not store where it can be exposed to direct sunlight

Refer to Application Data Sheet for Additional Precautions and Safe Handling Procedures

Refer to Application Data sheet for Additional Precautions and Safe Handling Procedures.

WARRANTY DISCLAIMER

The information contained herein is based on available data and is provided for information only. CRC™ makes no warranties, guarantees, or conditions, expressed or implied, regarding the accuracy of the data or its use therein. CRC™ will not be liable for any damages arising from the use of the information product described on this data sheet. Product data subject to change without notice. Unless otherwise stated, CRC™ sole warrantee shall be the replacement or refund of purchase price for any product found not to meet the above specification

CRC Coating Technologies Inc.™ 6254 Skyway RD, PO Box 915 Smithville, ON L0R 2A0	TEL: 289-448-0157 888-292-5565 FAX: 905-527-0606	Email: info@crccoatings.com www.crccoatings.com	CRC Coating Technologies Inc.™ 3909 Witmer RD, Suite 1014 Niagara Fall, NY 14305
--	--	---	--